

26990031A

1st auxiliary contact pre-break & position NO/NC SIRCO B3-8

Auxiliary contact for pre-breaking and 0 and I position signalling used to monitor the position of the switch disconnecter or to provide pre-break information.



General characteristics

- 1 to 2 NO/NC auxiliary contacts.
- 1 to 4 NO/NC auxiliary contacts.
- 1 to 2 low level NO/NC auxiliary contacts.

Access to resources (ex: manuals)



<https://www.socomec.co.in/en-in/reference/26990031A>

Classification

UNSPSC	39122233
ETIM Class	EC000041
IGCC	5290

Commerce

Effective date	2016-06-14
Offer Life Cycle Code	40
Country of origin	IN

ETIM - Electrical characteristics

Number of contacts as change-over contact	1
Rated operation current Ie at AC-15, 230 V [A]	4

ETIM - Mechanical characteristics

Type of electric connection	Flat plug-in connection
Mounting method	Front fastening

ETIM - Technical features

Model	Top mounting and integrable
Lamp holder	None

Logistics

GTIN/EAN	3596032956899
Customs number	8536500700
Price unit	PC
Weight of the packing unit [kg]	0.001
Length of the packing unit [m]	0.012
Width of the packing unit [m]	0.1
Depth of the packing unit [m]	0.16

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Number change-over contacts	1
Number NC contacts	1
Number NO contacts	1
Type	1st Pre-break auxiliary contact for frame B3..B8