

26AC3064

AC Load break switch SIRCO AC 690VDC 3P 630A



Strong points

- Reliability and performance
- Safety of property and personnel
- Simplicity
- Easy to install

General characteristics

- Fully visible breaking (double position window).
- Extreme usage categories (AC-22 and AC-23).
- High resistance to damp heat ("tropicalised" as standard).

Compliance with standards

- IEC 60947-3

Access to resources (ex: manuals)

<https://www.socomec.co.in/en-in/reference/26AC3064>

SIRCO AC units are manual or motorised multi-pole load break switches. They make and break under load conditions and provide safety isolation. SIRCO AC devices are designed for extreme applications up to 690 VAC - AC 23.

Classification

| | |
|------------|----------|
| UNSPSC | 39122233 |
| ETIM Class | EC000216 |
| IGCC | 5290 |

Commerce

| | |
|----------------------------|------------|
| Effective date | 2012-12-13 |
| Country of origin | FR |
| Length of the product unit | 0.26 |
| Width of the product unit | 0.23 |
| Depth of the product unit | 0.16 |
| Weight | 9.248 |

ETIM - Electrical characteristics

| | |
|---|----------|
| Max. rated operation voltage Ue AC [V] | 690 |
| Rated operating voltage [V] | 400..690 |
| Rated permanent current Iu [A] | 630 |
| Rated permanent current at AC-23, 400 V [A] | 630 |
| Rated permanent current at AC-21, 400 V [A] | 630 |
| Rated short-time withstand current Icw [kA] | 20 |
| Rated operation power at AC-23, 400 V [kW] | 375 |
| Switching power at 400 V [kW] | 375 |
| Conditioned rated short-circuit current Iq [kA] | 50 |
| Number of poles | 3 |

ETIM - Mechanical characteristics

| | |
|--|-------|
| Suitable for floor mounting | No |
| Suitable for front mounting 4-hole | No |
| Suitable for front mounting centre | No |
| Suitable for distribution board installation | No |
| Suitable for intermediate mounting | Yes |
| Colour control element | Other |
| Degree of protection (IP), front side | IP20 |

ETIM - Technical features

| | |
|---|--|
| Version as main switch | Yes |
| Version as maintenance-/service switch | Yes |
| Version as safety switch | Yes |
| Version as emergency stop installation | Yes |
| Version as reversing switch | No |
| Number of switches | 1 |
| Motor drive optional | No |
| Motor drive integrated | No |
| Voltage release optional | No |
| Device construction | Built-in device fixed built-in technique |
| Type of control element | Other |
| Interlockable | Yes |
| Type of electrical connection of main circuit | Bolt connection |

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596032721992 |
| Customs number | 8536508090 |
| Price unit | PC |
| Weight of the packing unit | 9.248 |
| Length of the packing unit | 0.157 |
| Width of the packing unit | 0.271 |
| Depth of the packing unit | 0.305 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|------------------|-----------------------------|
| Control operator | Direct : C2 / External : S4 |
| Number of poles | 3 |
| Rated voltage | 690 VAC |
| Rated current | 630 |
| Type | Front operation |
| Frame size | B6 |