26K14011A

AC Load break switch SIRCO 4P 125A

Strong points
- Reliability and performance
- Safety of property
- Simplicity
- Easy to install

SIRCO are manually or remotely operated multipolar load break switches.
As switch disconnector, they make and break under load conditions and provide safe isolation.
They are designed for heavy duty applications up to 415 VAC - AC 23. Supplied “tropicalized” as standard, they can be installed in any environment

General characteristics
- Double positive break indication given through a position indication window, located directly on the product, and by the operating handle.
- Severe load duty categories (AC-22 and AC-23).
- High resistance to damp heat (supplied "tropicalised").
- References includes switch, interphase barriers (exept frame B2) and direct handle.

Compliance with standards
- IS - IEC 60947-3

Access to resources (ex: manuals)

https://www.socomec.co.in/en-in/reference/26K14011A

=-=-=-=-=-=- System =-=-=-=-=-=-	
Fill rate E-Order Common	20
Fill rate E-Order Selection	89
Classification	
UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290
Commerce	
Effective date	2016-06-14
Country of origin	IN
Discount Policy	1CA32
Discount Policy Label	SIRCO<=630
ETIM - Electrical characteristics	
Max. rated operation voltage Ue AC [V]	415
Rated operating voltage [V]	415..415
Rated permanent current Iu [A]	125
Rated permanent current at AC-23, 400 V [A]	125
Rated permanent current at AC-21, 400 V [A]	125
Rated short-time withstand current Icw [kA]	2.5
Rated operation power at AC-23, 400 V [kW]	63
Switching power at 400 V [kW]	63
Conditioned rated short-circuit current Iq [kA]	50
Number of poles	4
ETIM - Mechanical characteristics	
Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	No
Colour control element	Other
Degree of protection (IP), front side	IP20
ETIM - Technical features	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique

Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

Logistics

GTIN/EAN	3596032957568
Customs number	8536508090
Price unit	PC
Weight of the packing unit	0.001

Norms

Conformity to standards	IEC

Technical Characteristics

Control operator	Direct : B1,J1 / External : S2
Number of poles	4
Rated current	125
Type	Front operation
Frame size	B2