

**41E14013A**

## ENCLOSED MANUAL TRANSFER SWITCH SIRCOVER 4X125A 415VAC FRAME B3

**Strong points**

- Safety
- Suitable for all kinds of environments
- Easy setup
- Extensive range

**General characteristics**

- 3 poles or 4 poles.
- Black handle.
- Painted steel enclosure, RAL 7035.
- Hinged door with double bar locking.

**Compliance with standards**

- IEC/IS 60947-6-1
- IEC 61439
- IEC 60204-1

**Access to resources (ex: manuals)**

<https://www.socomec.co.in/en-in/reference/41E14013A>

Enclosed changeover switches ensure the on-load changeover of circuits and safely isolate all low-voltage electrical circuits by providing protection against contact with live parts and environmental elements such as dust, water and other hazards. They safely switch sources or loads and enable the shutdown and isolation of the power supply as close to the equipment as possible.

**Classification**

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

**Commerce**

Effective date	2016-06-14
Country of origin	IN

**ETIM - Electrical characteristics**

Rated permanent current Iu [A]	4
Number of poles	4

**ETIM - Mechanical characteristics**

Suitable for floor mounting	Yes
Suitable for front mounting 4-hole	Yes
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	No
Colour control element	Black
Degree of protection (IP), front side	IP55

**ETIM - Technical features**

Version as main switch	No
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Complete device in housing
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

**Logistics**

GTIN/EAN	3596032960520
Customs number	8536508090
Price unit	PC
Weight of the packing unit	0.001

**Norms**

Conformity to standards	IEC
-------------------------	-----

**Technical Characteristics**

Number of poles	4
-----------------	---

Rated current	125
Size	2
Frame size	B3