

41K13320A

MANUAL TRANSFER SWITCH SIRCOVER 3X3200A DIRECT HANDLE KIT



Strong points

- A complete range
- Easy to connect
- Stable positions
- On-load switching

General characteristics

- Range from 125A to 3200A.
- Available in 3P or 4P.
- References includes switch, bridging bars up to 1600A, interphase barriers (except frame B2) and direct handle.

Compliance with standards

- IEC 60947-6-1
- IEC 60947-3
- GB/T 14048.11

Access to resources (ex: manuals)

<https://www.socomec.co.in/en-in/reference/41K13320A>

SIRCOVER provide open transition switching (I-O-II), on-load transfer between two sources for any low voltage power circuit, as well as safety isolation with double breaking per pole. In addition to source changeover function, they can as well be used for source inversion (e.g. to change the direction of a motor) or grounding/earthing. They are available in 3 or 4 poles.

| | |
|---|--|
| Classification | |
| ETIM Class | EC000216 |
| Commerce | |
| Effective date | 2016-06-14 |
| Country of origin | IN |
| ETIM - Electrical characteristics | |
| Rated permanent current Iu [A] | 3 |
| Number of poles | 3 |
| ETIM - Mechanical characteristics | |
| Suitable for floor mounting | No |
| Suitable for front mounting 4-hole | No |
| Suitable for front mounting centre | No |
| Suitable for distribution board installation | No |
| Suitable for intermediate mounting | Yes |
| Colour control element | Black |
| Degree of protection (IP), front side | IP20 |
| ETIM - Technical features | |
| Version as main switch | Yes |
| Version as maintenance-/service switch | Yes |
| Version as safety switch | Yes |
| Version as emergency stop installation | Yes |
| Version as reversing switch | Yes |
| Number of switches | 2 |
| Motor drive optional | No |
| Motor drive integrated | No |
| Voltage release optional | No |
| Device construction | Built-in device fixed built-in technique |
| Type of control element | Long turning handle |
| Interlockable | Yes |
| Type of electrical connection of main circuit | Bolt connection |
| Logistics | |
| GTIN/EAN | 3596032960834 |
| Customs number | 8536508090 |
| Price unit | PC |
| Weight of the packing unit | 0.001 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Application | Energy |
| Control operator | Direct : C2,S5 / External : S5 |
| Number of poles | 3 |
| Rated current | 3200 |

| | |
|------------|---------------|
| Type | Manual I-0-II |
| Frame size | B8 |