

**41K23050A**

## MANUAL TRANSFER SWITCH SIRCOVER 3X500A EXTERNAL HANDLE KIT



### Strong points

- A complete range
- Easy to connect
- Stable positions
- On-load switching

### General characteristics

- Range from 125A to 3200A.
- Available in 3P or 4P.
- References includes switch, bridging bars up to 1600A, interphase barriers (except frame B2), 200mm extension shaft and external handle.

### Compliance with standards

- IEC 60947-6-1
- IEC 60947-3
- GB/T 14048.11

### Access to resources (ex: manuals)

<https://www.socomec.co.in/en-in/reference/41K23050A>

SIRCOVER provide open transition switching (I-O-II), on-load transfer between two sources for any low voltage power circuit, as well as safety isolation with double breaking per pole. In addition to source changeover function, they can as well be used for source inversion (e.g. to change the direction of a motor) or grounding/earthing. They are available in 3 or 4 poles.

#### ----- System -----

Fill rate E-Order Common	33
Fill rate E-Order Selection	67

#### Classification

ETIM Class	EC000216
------------	----------

#### Commerce

Effective date	2016-06-14
Country of origin	IN
Discount Policy	1CH38
Discount Policy Label	SIRCOVER MII

#### ETIM - Electrical characteristics

Rated permanent current Iu [A]	3
Number of poles	3

#### ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Black
Degree of protection (IP), front side	IP20

#### ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

#### Logistics

GTIN/EAN	3596032961091
Customs number	8536508090
Price unit	PC
Weight of the packing unit	0.001

#### Norms

Conformity to standards	IEC
-------------------------	-----

#### Technical Characteristics

Application	Energy
Control operator	Direct : B3,J2 / External : S2
Number of poles	3
Rated current	500
Type	Manual I-0-II
Frame size	B5