

47506015

Closed toroid 15mm DELTA IP15



Strong points

- A complete range
- Number of fixing options (?IP and ?IP-R)
- Patented centring solution (?IP and ?IP-R)
- Quick to install and safe to use (?IP-R)

General characteristics

- Full range.
- Number of fixing options (?IP and ?IP-R).
- Patented centring solution (?IP and ?IP-R).
- Quick to install and safe to use (?IP-R).

Compliance with standards

- IEC 61869-1

Access to resources (ex: manuals)

<https://www.socomec.co.in/en-in/reference/47506015>

You need core balance transformers to install fault detection and locating units. These enclose the active conductors and highlight earth fault currents. Socomec core balance transformers meet measurement sensitivity needs and are suitable for ISOM Digiware locating systems. Closed (?IP, WR and TFR series) or split (?IP-R series), both types are suitable for all wiring configurations. The use of the ISOM T-15 adapter is required to connect the core balance transformers to ISOM Digiware F-60.

| | |
|--|--------------------|
| Classification | |
| UNSPSC | 39122309 |
| ETIM Class | EC002048 |
| IGCC | 5343 |
| Commerce | |
| Effective date | 2011-07-04 |
| Country of origin | FR |
| ETIM - Electrical characteristics | |
| Rated primary current [A] | 10 |
| Rated secondary current [A] | 0.016 |
| Rated secondary apparent power [VA] | 0.02 |
| Accuracy class | 3 |
| Overcurrent limiting factor | FS 5 |
| Calibrated | No |
| ETIM - Mechanical characteristics | |
| With contact protection | No |
| Opening diameter [mm] | 15 |
| Snap mounting | Yes |
| With copper rail | No |
| Secondary connection | Plug-in connection |
| ETIM - Technical features | |
| Model | Other |
| Number of primary inputs | 1 |
| Logistics | |
| GTIN/EAN | 3596032613785 |
| Customs number | 8504312990 |
| Price unit | PC |
| Weight of the packing unit | 0.156 |
| Length of the packing unit | 0.095 |
| Width of the packing unit | 0.065 |
| Depth of the packing unit | 0.05 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Model | DELTA IP 15 |
| Opening | Circular closed |
| Size | 15 mm |