

48250401G

Energy Meter Modular multifunction meter DIRIS A-10 with RS485 MODBUS



Strong points

- Easy to use
- Built-in temperature probe
- Detects wiring errors
- Conformity to with IEC 61557-12

Compliance with standards

- IEC 61557-12
- IEC 62053-22 Class 0.5 S
- IEC 62053-23 Class 2
- UL

Access to resources (ex: manuals)



<https://www.socomec.co.in/en-in/reference/48250401G>

The DIRIS A-10 is a multi-measurement device for measuring electrical values in LV networks in modular format with connection to current transformers.

It enables viewing of all electrical parameters and operation of measurement, metering and communication functions.

Classification

UNSPSC	83101808
ETIM Class	EC002301

Commerce

Description	DIRIS A-10 with Modbus communication protocols and RS485 communication ports It allows all electrical parameters to be displayed and utilised for communication and/or output functions
Effective date	2021-08-10
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Electrical characteristics

Accuracy class active energy according to IEC 62053-22	0.2S
Accuracy class reactive energy according to IEC 62053-23	Other
Sampling frequency [Hz]	65
Number of voltage measurement inputs	3
Number of current measurement inputs	3
Voltage type (supply voltage)	AC
Supply voltage AC 50 Hz [V]	110..277
Supply voltage AC 60 Hz [V]	110..277
Measuring range for frequency [Hz]	45..65

ETIM - Technical features

Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	Yes
Voltmeter	Yes
Effective power measurement device	Yes
Display	LCD
Remote display	No

Logistics

Customs number	9030310090
Price unit	PC
Weight of the packing unit [kg]	0,33

Technical Characteristics

Application	Monitoring
Communication ports	RS485
Communication protocols	Modbus
Model	A-10