

48250500G

Multifunction meter DIRIS A-40 RS485 MODBUS 3 inputs/2 outputs



Strong points

- Assisted configuration
- Integration made easy
- Connected to the Cloud
- IEC 61557-12 compliant

Compliance with standards

- IEC 61557-12
- EN 50160
- UL61010 E257746

Access to resources (ex: manuals)



<https://www.socomec.co.in/en-in/reference/48250500G>

The DIRIS A-40 is a performance monitoring device (PMD) in a 96 x96 format for door mounting. It is designed for measuring, monitoring and managing electrical energy.

The DIRIS A-40 offers a range of functions for measuring voltage, current, power, energy and quality. It enables analysis of a single-phase or three-phase load.

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Description	DIRIS A-40 3 inputs/2 outputs with Modbus communication protocols / RS485 communication ports door-mounted power monitoring device in 96 x 96 format, analysis of a single-phase or three-phase load
Effective date	2021-08-10
Offer Life Cycle Code	40
Country of origin	CN

ETIM - Electrical characteristics

Accuracy class active energy according to IEC 62053-22	0.25
Sampling frequency [Hz]	10
Number of voltage measurement inputs	5
Number of current measurement inputs	3
Voltage type (supply voltage)	DC
Supply voltage DC [V]	120..300
Measuring range for frequency [Hz]	45..65
Number of digital inputs	3
Number of digital outputs	2
Number of Ethernet-connections	1
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for other bus systems	No
Web server with HTTPS transfer protocol	No

ETIM - Mechanical characteristics

Width [mm]	98
Height [mm]	98
Depth [mm]	85

ETIM - Technical features

Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	Yes
Voltmeter	Yes
Effective power measurement device	Yes

Display	LCD
Remote display	No
Logistics	
Customs number	3926909790
Price unit	PC
Weight of the packing unit [kg]	0.2
Length of the packing unit [m]	0.11
Width of the packing unit [m]	0.12
Depth of the packing unit [m]	0.11
Norms	
Conformity to standards	IEC UL
Technical Characteristics	
Application	Analysis
Communication ports	RS485
Communication protocols	Modbus
Model	A40
Type	3 inputs/2 outputs