

48250501G

Multifunction meter DIRIS A-40 ethernet com. + RS485 MODBUS gateway I/O 3/2



Strong points

- Assisted configuration
- Facilitated integration
- Connected to the Cloud
- Compliant with IEC 61557-12

General characteristics

- Assisted configuration.
- Connected to the Cloud.
- Compliant with IEC 61557-12.
- Smart sensors.

Compliance with standards

- IEC 61557-12
- EN 50160
- UL61010 E257746

Access to resources (ex: manuals)

The DIRIS A-40 is a door-mounted power monitoring device (PMD) in 96 x 96 format. It is intended for the measurement, monitoring and management of electrical energy.

The DIRIS A-40 provides numerous functions for measuring voltage, current, power, energy and quality.

It allows the analysis of a single-phase or three-phase load.

Classification	
ETIM Class	EC002301
Commerce	
Effective date	2021-08-10
Country of origin	CN
Logistics	
Customs number	3926909790
Price unit	PC
Weight of the packing unit	0.41
Length of the packing unit	0.11
Width of the packing unit	0.11
Depth of the packing unit	0.12
Norms	
Conformity to standards	IEC br/>UL
Technical Characteristics	
Application	Analysis
Communication ports	RS485 + Ethernet
Communication protocols	Modbus
Model	A40
Туре	3 inputs/2 outputs

https://www.socomec.co.in/enin/reference/48250501G