

48250502G

## Multifunction meter DIRIS A-40 communication Sub D9 PROFIBUS DP I/O:3/2



### Strong points

- Assisted configuration
- Facilitated integration
- Connected to the Cloud
- Compliant with IEC 61557-12

### General characteristics

- Assisted configuration.
- Connected to the Cloud.
- Compliant with IEC 61557-12.
- Smart sensors.

### Compliance with standards

- IEC 61557-12
- EN 50160
- UL61010 E257746

### Access to resources (ex: manuals)

The DIRIS A-40 is a door-mounted power monitoring device (PMD) in 96 x 96 format. It is intended for the measurement, monitoring and management of electrical energy.

The DIRIS A-40 provides numerous functions for measuring voltage, current, power, energy and quality. It allows the analysis of a single-phase or three-phase load.

### Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

### Commerce

Effective date	2022-06-15
Country of origin	TN

### Logistics

Customs number	9030310090
Price unit	PC
Weight of the packing unit	0.425
Length of the packing unit	0.1
Width of the packing unit	0.12
Depth of the packing unit	0.11

### Norms

Conformity to standards	IEC UL
-------------------------	------------

### Technical Characteristics

Application	Analysis
Communication ports	Profibus DP
Communication protocols	Profibus
Model	A40
Type	3 inputs/2 outputs

<https://www.socomec.co.in/en-in/reference/48250502G>