

48290200G

Power monitoring device DIRIS Digiware D-30 Single-point display



Strong points

- Plug & Play
- Safe
- Dedicated display

General characteristics

- 96 x 96 mm panel mount format.
- 10 direct access buttons.
- Self-powerd via the RJ9 cable.

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Access to resources (ex: manuals)



<https://www.socomec.co.in/en-in/reference/48290200G>

The DIRIS D-30 is a remote display that can be connected to a DIRIS B power meter or a DIRIS Digiware I-4x current module via an RJ9 cable.

Classification

UNSPSC	83101808
ETIM Class	EC004862
IGCC	6042

Commerce

Description	Multifunction power meter DIRIS D-30 single-point display for DIRIS B PMD and DIRIS Digiware I-4x modules, 96x96 mm, communication ports RJ9 - USB, works with RJ12 smart current sensors
Effective date	2013-11-22
Offer Life Cycle Code	40

ETIM - Electrical characteristics

Supply voltage DC [V]	0..24
Voltage type (supply voltage)	DC

ETIM - Mechanical characteristics

Colour display	No
Number of colours of the display	2
Rail mounting possible	Yes
Wall mounting/direct mounting	Yes
Front built-in possible	Yes
Rack-assembly possible	No
Degree of protection (IP)	IP40
Width [mm]	18
Height [mm]	96
Depth [mm]	27
Operating temperature [°C]	-10..-70

ETIM - Technical features

Type of display	LCD
Number of grey-scales/blue-scales of display	10
Visible diagonal screen size [inch]	3.54
Number of pixels, horizontal	350
Number of pixels, vertical	160
With on-screen keyboard	Yes
With touch screen	No
Mouse-cursor control integrated	No
With HW-interface PS2	No
Suitable for safety functions	No

Logistics

Customs number	8528590090
Price unit	PC

Norms

Conformity to standards	IEC UL
-------------------------	------------

Technical Characteristics

Height [mm]	96
Width [mm]	18
Depth [mm]	27
Communication ports	RJ9 - USB
Model	D-30
Size	96x96 mm
Type	Single-point display for DIRIS B PMD and DIRIS Digiware I-4x modules