

**48290673**
**Strong points**

- Plug & Play
- Accuracy as per standard IEC 61557-12
- Safe locking mechanism
- Installation
- Simplified installation

**General characteristics**

- Range from 150 to 6000A.
- Used with DIRIS Digiware, DIRIS A-40 and DIRIS B.

**Compliance with standards**

- IEC 61557-12
- ISO 14025
- UL

**Access to resources (ex: manuals)**

TF flexible current sensors measure the load currents of an electrical circuit and send the data to meters and Power Monitoring Devices or current modules via an RJ12 plug-and-play connection. Thanks to a wide measurement range, TF current sensors cover a wide current range from 100 to 6000 A, with only 7 references. TF flexible current sensors can be used with DIRIS Digiware I modules, DIRIS A-40 and DIRIS B.

**Classification**

UNSPSC	83101808
ETIM Class	EC002048
IGCC	6042

**Commerce**

Effective date	2021-08-14
Obsolescence date	2021-08-15
Production ban date	2021-08-16
Country of origin	FR

**ETIM - Electrical characteristics**

Rated secondary current [A]	0.1
Rated secondary apparent power [VA]	0.1
Accuracy class	0.2
Overcurrent limiting factor	FS 10
Calibrated	Yes

**ETIM - Mechanical characteristics**

With contact protection	Yes
-------------------------	-----

**ETIM - Technical features**

Model	Attachable current transformer
-------	--------------------------------

**Logistics**

GTIN/EAN	3596033023835
Customs number	8504318090
Price unit	PC
Weight of the packing unit	0.25

**Norms**

Conformity to standards	IEC UL
-------------------------	------------

**Technical Characteristics**

Model	TF
-------	----

<https://www.socomec.co.in/en-in/reference/48290673>