

48290676
Strong points

- Plug & Play
- Accuracy as per standard IEC 61557-12
- Safe locking mechanism
- Installation
- Simplified installation

General characteristics

- Range from 150 to 6000A.
- Used with DIRIS Digiware, DIRIS A-40 and DIRIS B.

Compliance with standards

- IEC 61557-12
- ISO 14025
- UL

Access to resources (ex: manuals)

TF flexible current sensors measure the load currents of an electrical circuit and send the data to meters and Power Monitoring Devices or current modules via an RJ12 plug-and-play connection. Thanks to a wide measurement range, TF current sensors cover a wide current range from 100 to 6000 A, with only 7 references. TF flexible current sensors can be used with DIRIS Digiware I modules, DIRIS A-40 and DIRIS B.

Classification

UNSPSC	83101808
ETIM Class	EC002048
IGCC	6042

Commerce

Effective date	2021-08-14
Obsolescence date	2021-08-15
Production ban date	2021-08-16
Country of origin	FR

ETIM - Electrical characteristics

Rated secondary current [A]	0.1
Rated secondary apparent power [VA]	0.1
Accuracy class	0.2
Overcurrent limiting factor	FS 10
Calibrated	Yes

ETIM - Mechanical characteristics

With contact protection	Yes
-------------------------	-----

ETIM - Technical features

Model	Attachable current transformer
-------	--------------------------------

Logistics

GTIN/EAN	3596033023866
Customs number	8504318090
Price unit	PC
Weight of the packing unit	0.25

Norms

Conformity to standards	IEC UL
-------------------------	------------

Technical Characteristics

Model	TF
Opening	200
Rated current	200
Secondary rated current	RJ12

<https://www.socomec.co.in/en-in/reference/48290676>