

48503000

Active-energy meter COUNTIS E10 Direct 63A

Strong points

- RS485 (MODBUS) communication, M-Bus, Ethernet or pulse outputs
- Multi-tariff
- B+D module MID-certified

General characteristics

- Compact dimensions.
- Measurement accuracy: 1%.
- Displayed on backlit screen.
- Multi-measurement available on display.

Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62052-11
- EN 50470-1
- EN 50470-3

Access to resources (ex: manuals)

<https://www.socomec.co.in/en-in/reference/48503000>

The COUNTIS E1x is a modular energy meter displaying the energy (kWh, kVAh and kVA) and other measurements directly on its backlit LCD display. It is designed for single-phase load metering and is used for direct connections of up to 80 A.

Classification

UNSPSC	41113708
ETIM Class	EC001506
IGCC	6341

Commerce

Effective date	2008-12-09
Obsolescence date	2020-04-01
Production ban date	2020-08-04
Country of origin	FR

ETIM - Electrical characteristics

Nominal current (In) [A]	63
Max. current (Imax) [A]	1890
Nominal voltage (Un) N-L [V]	184..276
Frequency [Hz]	50..50
Accuracy class	B
Pole type	Single phase
Energy type	Effective power
Suitable for	Purchase
Tariff type	One-tariff
Measurement type load profile	No
Calibrated	Yes
Pulse output	None
Pulse type	D0
Pulse rate [Imp/kWh (kvarh)]	10..10

ETIM - Mechanical characteristics

Escapement mechanism	No
Mounting method	DRA (DIN-rail adapter)
Width in number of modular spacings	3
With lock code	Yes
Degree of protection (IP)	IP20

ETIM - Technical features

Type of meter	Electronic
Model	Direct measurement
Approval	Measuring Instruments Directive
Type of indication	Digital
Type of interface	None
EEC40 signature	No

Logistics

GTIN/EAN	3596031946839
Customs number	9028301100
Price unit	PC
Weight of the packing unit	0.24
Length of the packing unit	0.09
Width of the packing unit	0.105

Depth of the packing unit	0.135
Norms	
Conformity to standards	IEC
Technical Characteristics	
Application	Metering
Model	E10
Type	1PH up to 63A