

48503009

Active-energy meter COUNTIS E41 via CT dual tariff



Strong points

- RS485 (MODBUS), M-BUS, Ethernet
- communication or pulse outputs
- B+D module MID-certified
- Bi-directional metering
- Multi-measurement and load curve

General characteristics

- Measurement accuracy: 1 % / 0,5% (MID).
- Backlit LCD display.
- Multi-measurement available on display.

Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62053-11
- EN 50470-1
- EN 50470-3

Access to resources (ex: manuals)



https://www.socomec.co.in/enin/reference/48503009

The COUNTIS E4x is a modular electrical energy meter displaying the energy (kWh, kVArh and kVA) and other measurements directly on its backlit LCD display. It is designed for three-phase load metering with connection via CT and is suitable for applications of up to 12000 A.

COUNTIS E42, E44, E46 and E48 are MID certified.

Classification UNSPSC 41113708 ETIM Class EC001506 IGCC 6341 Commerce Effective date 2008-12-09 Obsolescence date 2020-04-01 Country of origin FR **ETIM - Electrical characteristics** Nominal current (In) [A] 6000 Max. current (Imax) [A] 3000 Nominal voltage (Un) N-L [V] 184..276 Nominal voltage (Un) L-L [V] 320..480 Frequency [Hz] 50..50 Accuracy class В Three conductor/four conductor Pole type Energy type Effective power Suitable for Purchase Tariff type One-tariff Tariff control External Measurement type load profile No Calibrated Yes Pulse output Electrical Pulse rate [Imp/kWh (kvarh)] 10..10 **ETIM - Mechanical characteristics** Escapement mechanism No Mounting method DRA (DIN-rail adapter) 4 Width in number of modular spacings With lock code Yes Degree of protection (IP) IP20 **ETIM - Technical features** Electronic Type of meter Model Measurement transformer Approval Measuring Instruments Directive Type of indication Digital EEC40 signature No Logistics GTIN/EAN 3596031946952 Customs number 9028301900 PC Price unit Weight of the packing unit 0.094 Length of the packing unit 0.12

COUNTIS E41 3PH CT/5A 2T



Width of the packing unit	0.085
Depth of the packing unit	0.03
Norms	
Conformity to standards	IEC
Technical Characteristics	
Application	Metering
Model	E41
Туре	3PH CT/5A, double-tariff