

48503038

Strong points

- RS485 (MODBUS) communication, M-Bus, Ethernet or pulse outputs
- Multi-tariff
- B+D module MID-certified

General characteristics

- Measurement accuracy: 1%.
- Displayed on backlit screen.
- Multi-measurement available on display.

Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62052-11
- EN 50470-1
- EN 50470-3

Access to resources (ex: manuals)

The COUNTIS E2x is a modular energy meter displaying the energy (kWh, kVArh and kVA) and other measurements directly on its backlit LCD display. It is designed for three-phase networks and allows a direct connection of up to 80 A.

| Classification | |
|--|------------------------|
| UNSPSC | 41113708 |
| ETIM Class | EC001506 |
| IGCC | 6341 |
| Commerce | |
| Effective date | 2013-03-20 |
| Obsolescence date | 2020-12-31 |
| Production ban date | 2020-12-31 |
| Country of origin | IT |
| ETIM - Electrical characteristics | S |
| Pulse rate [Imp/kWh (kvarh)] | 1010 |
| ETIM - Mechanical characteristi | ics |
| Mounting method | DRA (DIN-rail adapter) |
| ETIM - Technical features | |
| Type of meter | Electronic |
| Type of indication | Digital |
| Logistics | |
| GTIN/EAN | 3596032740337 |
| Customs number | 9028301900 |
| Price unit | PC |
| Weight of the packing unit | 0.384 |
| Length of the packing unit | 0.09 |
| Width of the packing unit | 0.08 |
| Depth of the packing unit | 0.1 |
| Technical Characteristics | |
| Application | Metering |
| Communication ports | M-BUS |
| Model | E26 |
| Туре | 3PH up to 63A, MID |

https://www.socomec.co.in/en-in/reference/48503038

2024-04-26 08:48:45