

48503048

Active-energy meter COUNTIS E18 80A dual tariff com ethernet Modbus TCP + MID



Strong points

- RS485 (MODBUS) communication, M-Bus, Ethernet or pulse outputs

- Multi-tariff

- B+D module MID-certified

General characteristics

- Compact dimensions.

- Measurement accuracy: 1%.

- Displayed on backlit screen.

- Multi-measurement available on display.

Compliance with standards

- IEC 62053-21 Class 1

- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62052-11
- EN 50470-1
- EN 50470-3

Access to resources (ex: manuals)



https://www.socomec.co.in/enin/reference/48503048

The COUNTIS E1x is a modular energy meter displaying the energy (kWh, kVArh and kVA) and other measurements directly on its backlit LCD display. It is designed for single-phase load metering and is used for direct connections of up to 80 A.

JNSPSC	41113708
ETIM Class	EC001506
IGCC	6341
Commerce	
Effective date	2016-04-12
Country of origin	IT
ETIM - Electrical characteristics	
Nominal current (In) [A]	80
Max. current (Imax) [A]	80
Nominal voltage (Un) N-L [V]	184276
Nominal voltage (Un) L-L [V]	320480
Frequency [Hz]	5060
Accuracy class	В
Pole type	Single phase
Energy type	Effective power and blind power
Suitable for	Purchase/supply
Tariff type	Two-tariff
Tariff control	External
Measurement type load profile	No
Calibrated	Yes
Pulse output	Electrical
Pulse rate [Imp/kWh (kvarh)]	1010
ETIM - Mechanical characteristics	•
Escapement mechanism	No
Mounting method	DRA (DIN-rail adapter)
Width in number of modular spacings	4
With lock code	No
Degree of protection (IP)	IP20
ETIM - Technical features	
Type of meter	Electronic
Model	Direct measurement
Approval	Measuring Instruments Directive
Type of indication	Digital
Type of interface	Other
EEC40 signature	No
Logistics	
GTIN/EAN	3596032942434
Customs number	9028301100
Price unit	PC
Weight of the packing unit	0.27
Length of the packing unit	0.09
Width of the packing unit	0.05

COUNTIS E18 1PH 80A ETH MID



Depth of the packing unit	0.11	
Norms		
Conformity to standards	IEC	
Technical Characteristics		
Application	Metering	
Communication ports	Ethernet	
Model	E18	
Туре	1PH up to 80A, MID	