

## 48503054

# Active-energy meter COUNTIS E27 Direct 80A dual tariff Ethernet Modbus TCP com.



#### Strong points

- RS485 (MODBUS) communication, M-
- Bus, Ethernet or pulse outputs
- Multi-tariff
- B+D module MID-certified

#### General characteristics

- Measurement accuracy: 1%.
- Displayed on backlit screen.
- Multi-measurement available on
- display.

#### Compliance with standards

- IEC 62053-21 Class 1
- IEC 62053-23 Class 2
- IEC 62053-31
- IEC 62052-11
- EN 50470-1
- EN 50470-3

Access to resources (ex: manuals)



https://www.socomec.co.in/enin/reference/48503054

The COUNTIS E2x is a modular energy meter displaying the energy (kWh, kVArh and kVA) and other measurements directly on its backlit LCD display. It is designed for three-phase networks and allows a direct connection of up to 80 A.

| UNSPSC                                   | 41113708                        |
|--|---------------------------------|
| ETIM Class                               | EC001506                        |
| IGCC                                     | 6341                            |
| Commerce                                 |                                 |
| Effective date                           | 2016-04-12                      |
| Country of origin                        | IT                              |
| ETIM - Electrical characteristics        |                                 |
| Nominal current (In) [A]                 | 80                              |
| Max. current (Imax) [A]                  | 80                              |
| Nominal voltage (Un) N-L [V]             | 184276                          |
| Nominal voltage (Un) L-L [V]             | 320480                          |
| Frequency [Hz]                           | 5060                            |
| Accuracy class                           | В                               |
| Pole type                                | Three conductor/four conductor  |
| Energy type                              | Effective power and blind power |
| Suitable for                             | Purchase/supply                 |
| Tariff type                              | Two-tariff                      |
| Tariff control                           | External                        |
| Measurement type load profile            | No                              |
| Calibrated                               | Yes                             |
| Pulse output                             | Electrical                      |
| Pulse type                               | SO                              |
| Pulse rate [Imp/kWh (kvarh)]             | 1010                            |
| <b>ETIM - Mechanical characteristics</b> | <b>i</b>                        |
| Escapement mechanism                     | No                              |
| Mounting method                          | DRA (DIN-rail adapter)          |
| Width in number of modular spacings      | 4                               |
| With lock code                           | No                              |
| Degree of protection (IP)                | IP20                            |
| ETIM - Technical features                |                                 |
| Type of meter                            | Electronic                      |
| Model                                    | Direct measurement              |
| Approval                                 | Domestic                        |
| Type of indication                       | Digital                         |
| Type of interface                        | Other                           |
| EEC40 signature                          | No                              |
| Logistics                                |                                 |
| GTIN/EAN                                 | 3596032942496                   |
| Customs number                           | 9028301900                      |
| Price unit                               | PC                              |
| Weight of the packing unit               | 0.57                            |
| Length of the packing unit               | 0.12                            |

### COUNTIS E27 3PH 80A ETH



| Width of the packing unit | 0.105         |
|---------------------------|---------------|
| Depth of the packing unit | 0.095         |
| Norms                     |               |
| Conformity to standards   | IEC           |
| Technical Characteristics |               |
| Application               | Metering      |
| Communication ports       | Ethernet      |
| Model                     | E27           |
| Туре                      | 3PH up to 80A |